





Equiplite™ High-Load | Dual sheave Blocks

Equiplite™ Dual Sheave Block use DSK 75 ULTRA loops to take the loads directly through the centre of the sheave. This allows the blocks to be extremely light (at least 75% less than competitive assemblies of the same load).

Compact, less windage, quick and easy to operate, compared to competitive blocks, of the same load. Even with cold & wet hands.

Dual sheave blocks are used on cruising boats and even on motor yachts like Ilona (to fix the dinghy and helicopter), and top competitive boats: TP52 Quantum Sails, Bribon..... .

For:

Out board and mainsheet systems

Vang blocks

Custom applications

High-strength material— low friction, impact resistant

The Dual sheave blocks use moulded carbon composite side plates, with high-tensile Hardkote-anodized aluminium sheaves for high load types. The bearings have an advanced high load low friction polymer bearing technology, giving unparalleled loaded friction efficiency of at least 92% (with dry operation, without need for lubrication). Dual sheave blocks have unmatched impact and wear resistance.

Reduced possible damage to the yacht, safe

With our compact loop system and clean protection reduces damage to the yacht. Safer: Extremely light weight reduces risk of injury when flogging.



Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs.

Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

All prices are retail prices in Euro.

All data approx and subject to change without notice.

Other sizes available on special order.

Unspecified dims. mm.
Break load approx. 2 x MWL.

DS: Dual Sheave Block

Other throats available

Part	Sheave Ø	Max. Line (mm)	Throat (mm)	MWL (kg)	Wt. (g)
50-150-18 DS-HL	150	35	65	30,000	3.360
50-135-16 DS-HL	135	35	60	23,000	2.940
50-125-14 DS-HL	125	35	55	18,000	2.730
35-120-14 DS-HL	120	32	47	18,000	2.240
50-120-12 DS-HL	120	35	55	13,000	2.380
35-120-12 DS-HL	120	32	47	13,000	2.138
35-95-12 DS-HL	95	26	47	13,000	1.610
25-98-10 DS-HL	78	25	45	8,000	840
25-78-10 DS-HL	78	25	45	8,000	819
20-75-8 DS-HL	75	22	35	6,000	539
20-65-8 DS-HL	65	20	35	6,000	539
18-64-7 DS-HL	64	16	30	5,000	431
18-64-6 DS-HL	64	16	30	4,000	405
16-46-6 DS-HL	47	16	27	4,000	221
14-47-5 DS-HL	47	13	22	3,000	187
14-40-5 DS-HL	39	13	20	3,000	136