





Equiplite™

Low load | Swiveling Connectors

Swivel connector for production and cruising yachts SLL LL Line

The SLL swiveling connector has arrived on the market with a quick loop, similar to our **Equiplite High Load** connector.

We have special designed these connectors for production and cruising yachts >20` - <45` These Low Load connectors are up to 80% lighter compared with traditional stainless connectors of the same load.

Swivel quick connectors are used on cruising and top competitive boats for:

Mast top halyards | **Jib | Genoa | Staysail halyards**
Tack fittings | **Genakker sheets**

High-strength material— low friction, impact resistant

Swivel quick connectors are produced with high tensile stainless steel. High load polymer bearing technology has been used to guarantee smooth rotation in all circumstances. The Swivels have unmatched impact - and wear resistance.

Reduced damage to the rig, safe and will not jam if overload.

Our compact swivel quick connector with Velcro wrap reduces damage to the Rig. Safer: light weight reduces risk of injury when flogging, reduces damage to masts, spinnaker tracks, topsides etc. Will not jam even if overloaded, will operate even when close to break load.

Two in one system

Which makes the system as compact as possible, for MAX. luff length and sail performance.





Note: Matching parts should be rounded, smooth, and with no sharp edges or burrs.
 Dyneema loops are coated with an UV coating, recoat when worn for long life. It is recommended that loops should be replaced when worn.

All prices are retail prices in Euro.
All data approx and subject to change without notice.
Other sizes available on special order.

Unspecified dims. mm.
Break load approx. 2 x MWL.

Part Low load version	Max. line (mm)	Throat (mm)	MWL (kg)	Wt. (g)
14-07 SLL	14	35	4,000	190
12-06 SLL	12	30	3,400	140
10-05 SLL	10	25	2,400	59
8-04 SLL	8	20	1,700	38
6-03 SLL	6	15	900	19